

XL-R 810



Baja Designs Features:

- **Satisfaction Guaranteed** - 30 Day Money Back Guarantee
- **Limited Lifetime Warranty** - Complete Purchase Protection
- **uService®** - Replaceable Lenses And Optics
- **ClearView®** - All The Light, Right Where You Need It
- **MoistureBlock™** - Waterproof, Rain Proof, Submersible
- **CopperDrive®** - Only LED Driven At 100%
- **5000K Daylight** - Less Driver Fatigue, Natural Color

Standards of Compliance:

- **MIL-STD-810G Certified** - (Low Temperature Test, High Temperature, Temperature & Humidity, Thermal Shock Cycling, Dust, Random Vibration, Mechanical Shock, Low Pressure, & Drip Box Water)
- **Exceeds MIL-STD810G**
- **Built-In Overvoltage Protection**
- **IP69k Certified** – (Submersible to 9ft)
- **IK10 Compliant** – (Mechanical Impact Testing)
- **Salt Spray Certified**

Specifications:

- **Lumens:** 9,500 Utilizing 4 Cree XHP50 LEDs
- **Candela:** 213,605 (CD)
- **Weight:** 2.45 lbs
- **Wattage/Amps:** 80W / 5.79A
- **Dimensions:** 5.24" x 3.65" x 5.24"
- **LED Life Expectancy:** 49,930 Hours
- **Front Lens:** Hard Coated Polycarbonate
- **Housing:** Hard Anodize & Powder Coat
- **Bezel:** Hard Anodize
- **Hardware & Bracket Material:** Stainless Steel





Part Number	Description	Raw Lumens Output	Watts Input	L inches	W inches	H inches	Weight (lb)
Driving Combo							
76-0003	XL-R 80, Driving Combo	9,500	80	5.24	3.65	5.24	2.45
Wide Cornering							
76-0005	XL-R 80, Wide Cornering	9,500	80	5.24	3.65	5.24	2.45
Amber Driving Combo							
76-0013	XL-R 80, Amber Driving Combo	9,500	80	5.24	3.65	5.24	2.45
Amber Wide Cornering							
76-0015	XL-R 80, Amber Wide Cornering	9,500	80	5.24	3.65	5.24	2.45
PAIR Driving Combo							
76-7803	XL-R 80, Pair, Driving Combo	19,000	160	5.24	3.65	5.24	4.90
PAIR Wide Cornering							
76-7805	XL-R 80, Pair, Wide Cornering	19,000	160	5.25	3.65	5.24	4.90
PAIR Amber Driving Combo							
76-7813	XL-R 80, Pair, Amber Driving Combo	19,000	160	5.25	3.65	5.24	4.90
PAIR Amber Wide Cornering							
76-7815	XL-R 80, Pair, Amber Wide Cornering	19,000	160	5.25	3.65	5.24	4.90

XL-R™ 810

